



REVISIONS				
REV	DESCRIPTION	DATE	INITIAL	APPROVED



		RED BARN MACHINE	
TITLE			
SLING, M/R HEAD 5 BLADE			
DWG NO.		RBE332A91-3191-00	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XX ± .005 .XX ± .01 X ± .1 FRACTIONS ± 1/32 ANGLES ± 5°		DRAWN BY: GILBERT APPROVED <i>D Weid</i> HEAT TREAT FINISH SPEC	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING		USED ON MODEL EUROCOPTER	
SCALE	1:8	DATE	4/21/2011
		SHEET 1 OF 19	

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS			
REV	DESCRIPTION	DATE	INITIAL
			APPROVED




ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	1	LIFTING EYE	A36PO	3/8 X 2-7/8 X 6-3/4	3
			-3	3	CONNECTOR ROD	1018	Ø2 X 17	4
			-5	3	BUTTON	BRONZE	Ø2 X 1	5
			-7	3	CONNECTOR HOOK	A36PO	5/8 X 5-1/2 X 5-3/4	6
			-9	3	STOP DISK	A36PO	1/4 X 2 X 2	7
	X		-11	1	WELDMENT			8
	1		-13		MAIN TUBE	CARBON STEEL	3 X 3 X 3/16 WALL X 30-1/4	9
	1		-15		CROSS TUBE	CARBON STEEL	3 X 3 X 3/16 WALL X 23-1/2	10
	2		-17		GUSSET	A36PO	1/4 X 6-1/2 X 3-1/4	11
	3		-19		TUBE CAP	A36PO	1/8 X 3 X 3	
	1		-21		MOUNT PLATE	A36PO	1/4 X 3-1/4 X 10-1/2	13
	2		-23		PIVOT PLATE	A36PO	3/16 X 3-1/2 X 10-1/2	14
	1		-25		ROD	1018	Ø7/8 x 4-3/4	15
	3		-27		PIVOT TUBE	1018	Ø2-1/2 X 3-1/2	16
		B/O	-31	1	GRIP	PVC	FLANGED Ø7/8 MCMaster-CARR #97045K23	1
		B/O	-33	3	CASTLE NUT	STEL	M16 X 2 MCMaster-CARR #93760A328	1
		B/O	-35	3	FLAT WASHER	STEEL	M16 MCMaster-CARR #91166A310	1
		B/O	-37	3	PLUG	PLASTIC	TO BE DETERMINED	1
		B/O	-39	3	BALL LOCK PIN	STAINLESS STEEL	1/4 X 2 MCMaster-CARR #92384A038	1
		B/O	-41	3	PIN	STEEL	5/8 X 2 MCMaster-CARR #97245A455	1
		B/O	-43	1	PIN	STEEL	5/8 X 1-1/4 MCMaster-CARR #98306A491	1
		B/O	-45	1	PIN	STEEL	1/2 X 1-13/32 MCMaster-CARR #93890A473	1
		B/O	-47	1	DOUBLE LOOP CLIP	STEEL	G.L. HUYETT #BPD-0118	1
		B/O	-49	2	LANYARD	S.S.	6" LOOP/LOOP MCMaster-CARR #90312A150	1
		B/O	-51	3	LANYARD	S.S.	18" LOOP/LOOP MCMaster-CARR #90312A360	1
		B/O	-53	9	SPLIT RING	STEEL	7/8 MCMaster-CARR #90177A217	1
		B/O	-55	7	COTTER PIN	STEEL	1/8 X 1-1/2 MCMaster-CARR #98338A190	1
		B/O	-57	3	COTTER PIN	STEEL	1/8 X 2 MCMaster-CARR #98338A200	1
		B/O	-59	2	LABEL	VINYL	SIGNS NOW	17
		B/O	-61	1	RED BARN PLACARD	ALUMINUM	RB41009	18
		B/O	-63	4	#2 DRIVE SCREW	COATED STEEL		1
	ASSY -11							

 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
TOLERANCES ON: DECIMALS .XXX ± .005 .XX ± .01 .X ± .1	
FRACTIONS ± 1/32 ANGLES ± 5°	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
DRAWN BY: GILBERT APPROVED: <i>D Weil</i> HEAT TREAT FINISH SPEC USED ON MODEL EUROCOPTER	
SCALE 1:16	DATE 4/21/2011
SHEET 2 OF 19	

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS			
REV	DESCRIPTION	DATE	INITIAL





NOTE: .03 DEEP GROOVE AS SHOWN, THIS SIDE ONLY , TO BE INKED AFTER POWDER COAT.

(-1)
LIFTING EYE


 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-1	REV 1
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX ± .005 .XX ± .01 .X ± .1 FRACTIONS ± 1/32 ANGLES ± 5°	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
DRAWN BY: GILBERT APPROVED: <i>D Weil</i> HEAT TREAT: FINISH POWDER COAT: YELLOW SPEC: FED #13538 USED ON MODEL: EUROPTER	
SCALE 1:2	DATE 4/21/2011
SHEET 3 OF 19	

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS			
REV	DESCRIPTION	DATE	INITIAL







(-3)
CONNECTOR ROD

 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-3	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX ± .005 .XX ± .01 .X ± .1 FRACTIONS ± 1/32 ANGLES ± 5°	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
SCALE 1:4	DATE 4/21/2011
SHEET 4 OF 19	

DRAWN BY:	GILBERT
APPROVED	<i>D Weil</i>
HEAT TREAT	POWDER COAT YELLOW
SPEC	FED #13538
USED ON MODEL	EUROCOPTER


This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS				
REV	DESCRIPTION	DATE	INITIAL	APPROVED






SECTION B-B

(-5)
BUTTON

 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-5	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX ± .005 .XX ± .01 .X ± .1 FRACTIONS ± 1/32 ANGLES ± 5°	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
DRAWN BY: GILBERT APPROVED: <i>D Weil</i> HEAT TREAT FINISH SPEC USED ON MODEL EUROCOPTER	
SCALE 1:2	DATE 4/21/2011
SHEET 5 OF 19	


This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.


REVISIONS				
REV	DESCRIPTION	DATE	INITIAL	APPROVED



-7



CONNECTOR HOOK

 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-7	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX ± .005 .XX ± .01 .X ± .1 FRACTIONS ± 1/32 ANGLES ± 5°	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
SCALE 1:3	DATE 4/21/2011
SHEET 6 OF 19	

DRAWN BY: GILBERT
APPROVED 
HEAT TREAT FINISH POWDER COAT YELLOW
SPEC FED #13538
USED ON MODEL EUROCOPTER


This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS				
REV	DESCRIPTION	DATE	INITIAL	APPROVED



(-9)




STOP DISK

 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-9	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX ± .005 FRACTIONS ± 1/32 .XX ± .01 ANGLES ± 5° .X ± .1	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
SCALE 1:2	DATE 4/21/2011
SHEET 7 OF 19	

DRAWN BY: GILBERT
APPROVED <i>D Weil</i>
HEAT TREAT
FINISH POWDER COAT YELLOW
SPEC FED #13538
USED ON MODEL
EUROCOPTER

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS			
REV	DESCRIPTION	DATE	INITIAL



SEE NOTE 1

- NOTE: 1. WELD ITEMS 23 IN PLACE WITH GROOVED
PIECE TO OUTSIDE AS SHOWN
2. WELD ALL SEAMS 100%.
3. REMOVE ALL WELD SPLATTER.




WELDMENT

RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-11	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
TOLERANCES ON: DECIMALS .XXX ± .005 .XX ± .01 .X ± .1	
FRACTIONS ± 1/32 ANGLES ± 5°	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
SCALE 1:12	DATE 4/21/2011
SHEET 8 OF 19	

DRAWN BY: GILBERT
APPROVED <i>D Weil</i>
HEAT TREAT FINISH POWDER COAT YELLOW
SPEC FED #13538
USED ON MODEL EUROCOPTER

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS				
REV	DESCRIPTION	DATE	INITIAL	APPROVED



(-13)



MAIN TUBE

 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-13	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX ± .005 .XX ± .01 .X ± .1 FRACTIONS ± 1/32 ANGLES ± 5°	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
SCALE 1:8	DATE 4/21/2011
SHEET 9 OF 19	

DRAWN BY: GILBERT APPROVED: <i>D Weil</i> HEAT TREAT FINISH: SPEC: USED ON MODEL: EUROCOPTER

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS				
REV	DESCRIPTION	DATE	INITIAL	APPROVED






(-15)
CROSS TUBE

 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-15	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
TOLERANCES ON: DECIMALS .XXX $\pm .005$.XX $\pm .01$.X $\pm .1$	
FRACTIONS $\pm 1/32$ ANGLES $\pm 5^\circ$	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
SCALE 1:8	DATE 4/21/2011
SHEET 10 OF 19	

DRAWN BY: GILBERT
APPROVED 
HEAT TREAT FINISH
SPEC
USED ON MODEL EUROCOPTER

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine

REVISIONS				
REV	DESCRIPTION	DATE	INITIAL	APPROVED






(-17)
GUSSET

 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-17	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX ± .005 FRACTIONS ± 1/32 .XX ± .01 ANGLES ± 5° .X ± .1	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
DRAWN BY: GILBERT APPROVED: <i>D Weil</i> HEAT TREAT FINISH SPEC USED ON MODEL EUROCOPTER	
SCALE 1:3	DATE 4/21/2011
SHEET 11 OF 19	

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine

REVISIONS			
REV	DESCRIPTION	DATE	INITIAL
APPROVED			






-19

TUBE CAP

 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-19	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX ± .005 .XX ± .01 .X ± .1 FRACTIONS ± 1/32 ANGLES ± 5°	DRAWN BY: GILBERT APPROVED <i>D Weil</i> HEAT TREAT FINISH SPEC
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	USED ON MODEL EUROCOPTER
SCALE 1:2	DATE 4/21/2011
SHEET 12 OF 19	

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine

REVISIONS				
REV	DESCRIPTION	DATE	INITIAL	APPROVED




(-21)

MOUNT PLATE

 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-21	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
TOLERANCES ON: DECIMALS .XXX ± .005 .XX ± .01 .X ± .1	
FRACTIONS ± 1/32 ANGLES ± 5°	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
DRAWN BY: GILBERT APPROVED <i>D Weil</i> HEAT TREAT FINISH SPEC USED ON MODEL EUROCOPTER	
SCALE 1:3	DATE 4/21/2011
SHEET 13 OF 19	

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine

REVISIONS			
REV	DESCRIPTION	DATE	INITIAL



NOTE: .03 DEEP GROOVE AS SHOWN, THIS SIDE ONLY , TO BE INKED AFTER POWDER COAT. GROOVE 1 OF 2 NEEDED PER ASSY.




(-23)

PIVOT PLATE

 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-23	REV 1
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX ± .005 .XX ± .01 .X ± .1 FRACTIONS ± 1/32 ANGLES ± 5°	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
DRAWN BY: GILBERT APPROVED: <i>D Weil</i> HEAT TREAT FINISH SPEC USED ON MODEL EUROCOPTER	
SCALE 1:4	DATE 4/21/2011
SHEET 14 OF 19	


This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine

REVISIONS				
REV	DESCRIPTION	DATE	INITIAL	APPROVED






(-25)

ROD


 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-25	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX $\pm .005$.XX $\pm .01$.X $\pm .1$	DRAWN BY: GILBERT APPROVED: <i>D Weil</i> HEAT TREAT FINISH SPEC
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	USED ON MODEL EUROCOPTER
SCALE 1:2	DATE 4/21/2011
SHEET 15 OF 19	

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS			
REV	DESCRIPTION	DATE	INITIAL



SECTION C-C



(-27)

PIVOT TUBE


 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-27	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX ± .005 FRACTIONS ± 1/32 .XX ± .01 ANGLES ± 5° .X ± .1	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
DRAWN BY: GILBERT APPROVED: <i>D Weil</i> HEAT TREAT: FINISH: SPEC:	
USED ON MODEL EUROCOPTER	
SCALE 1:2	DATE 4/21/2011
SHEET 16 OF 19	

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS				
REV	DESCRIPTION	DATE	INITIAL	APPROVED

FRONT

.38



.30

2.32

RBE332A91-3191-00

.25

NOTE: BLACK LETTERS, ADHESIVE BACK, ARIAL FONT


-59

LABEL


 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-59	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
TOLERANCES ON: DECIMALS .XXX ± .005 .XX ± .01 .X ± .1	
FRACTIONS ± 1/32 ANGLES ± 5°	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
DRAWN BY: GILBERT APPROVED: <i>D Weil</i> HEAT TREAT FINISH SPEC USED ON MODEL EUROCOPTER	
SCALE 1:1	DATE 4/21/2011
SHEET 17 OF 19	

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS				
REV	DESCRIPTION	DATE	INITIAL	APPROVED



NOTE: ENGRAVE AS SHOWN


 RED BARN MACHINE	
TITLE SLING, M/R HEAD 5 BLADE	
DWG NO. RBE332A91-3191-00-61	REV
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
TOLERANCES ON: DECIMALS .XXX ± .005 FRACTIONS ± 1/32 .XX ± .01 ANGLES ± 5° .X ± .1	
DRAWN BY: GILBERT	
APPROVED <i>D Weil</i>	
HEAT TREAT FINISH	
SPEC	
UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
USED ON MODEL EUROCOPTER	
SCALE 1:1	DATE 4/21/2011
SHEET 18 OF 19	

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS				
REV	DESCRIPTION	DATE	INITIAL	APPROVED

RED BARN MACHINE
190 S. DANEBO AVE., EUGENE OR. 97402
(541)344-9953; fax (541)344-3863
e-mail; sales@redbarn.net

FIRST ARTICLE WEIGHT TEST



INSPECTION & TESTING PROCEDURES FOR THE RBE332A91-3191-00, SLING, M/R HEAD 5 BLADE. THIS ASSEMBLY IS DESIGNED EXCLUSIVELY FOR HOISTING AND INSTALLING/REMOVING THE 5-BLADED MAIN ROTOR HEAD. THIS ASSEMBLY SHOULD BE INSPECTED BEFORE EACH USE. REPLACE ANY ITEMS THAT ARE DAMAGED OR SUSPECTED OF DAMAGE BEFORE USING!

FIRST ARTICLE WEIGHT TEST

1. AFTER INSPECTION, PLACE SLING ASSEMBLY ON A OVERHEAD LIFTING DEVICE. ATTACH 3 CONNECTOR HOOKS TO AN APPROAITE TEST WEIGHT OF 5845 LBS, USE BALL LOCK PINS TO LOCK INTO FIXTURE.
2. LIFT WEIGHT FOR AT LEAST 5 MINUTES, CONTINUALLY CHECKING FOR CRACKS, DEFLECTION, OR DISTORTION.
3. REMOVE WEIGHT AND RE-INSPECT SLING, CHECKING FOR STRESS CRACKS, BENDING, OR DISTORTIONS.

INSPECTOR _____

TESTER _____

S.N. _____

DATE _____

RED BARN MACHINE		
TITLE	SLING, M/R HEAD 5 BLADE	
DWG NO.	RBE332A91-3191-00	REV